

IN THE CLAIMS

Claims pending

- At time of the Action: Claims 1-20
- After this Response: Claims 1-20

Canceled or Withdrawn claims: None

Amended claims: Claims 1, 8 and 15

New claims: None

1. (Currently Amended) A method comprising:

receiving first data to be blindly signed;

establishing parameter data for use with signature generating logic that encrypts data based on a Jacobian of at least one curve, said parameter data causing said signature generating logic to select at least one Gap Diffie-Hellman (GDH) group of elements relating to said curve;

determining private key data and corresponding public key data using said signature generating logic;

generating second data by signing said first data with said private key data using said signature generating logic, said second data having a corresponding blind digital signature, said blind digital signature having a length corresponding to a single element in said Jacobian of said at least one curve; and

disseminating the second data to a computing device.

2. **(Previously Amended)** The method as recited in claim 1, further comprising generating said first data by:

digitally signing a message $m \in \{0,1\}^*$,

determining $h = h(m) \in G$,

selecting a random $r \in Z_P^*$ and

setting $h' = r \cdot h \in G$, wherein said first data includes h' and Z_P^* is a multiplicative group.

3. **(Original)** The method as recited in claim 2, wherein said parameter data establishes a base group G of order p and generator g as system parameters for said signature generating logic.

4. **(Previously Amended)** The method as recited in claim 3, wherein determining said private key data and said public key data includes:

picking

$$x \xleftarrow{R} Z_P^*,$$

and

computing $v \leftrightarrow g^x$, wherein said public key data includes v , said private key data includes x , and Z_P^* is a multiplicative group.

5. **(Original)** The method as recited in claim 4, wherein generating second data by signing said first data further includes:

signing h' by computing $\sigma' = x \cdot h' \in G$.

6. **(Original)** The method as recited in claim 5, further comprising:
determining if said blind digital signature is valid.

7. **(Previously Amended)** The method as recited in claim 6, wherein
determining if said blind digital signature is valid further includes:

obtaining a GDH signature on h by computing $\sigma = r \cdot \sigma' \in G$ where $r' = r^{-1}$
mod p and $\sigma = x \cdot h \in G$ is a valid GDH signature on m ; and
determining if (g, v, h, σ) is a valid Diffie-Hellman tuple.

8. **(Currently Amended)** A computer-readable medium having computer-
implementable instructions for performing acts comprising:

receiving first data to be blindly signed;

configuring signature generating logic using parameter data so as to be
capable of encrypting data based on a Jacobian of at least one curve, said
parameter data causing said signature generating logic to select at least one Gap
Diffie-Hellman (GDH) group of elements relating to said curve;

determining private key data and corresponding public key data using said
signature generating logic;

generating second data by signing said first data with said private key data
using said signature generating logic, said second data having a corresponding
blind digital signature, said blind digital signature having a length corresponding
to a single element in said Jacobian of said at least one curve; and

disseminating the second data to a computing device.

9. **(Previously Amended)** The computer-readable medium as recited in claim 8, having computer-implementable instructions for performing further acts comprising:

generating said first data by digitally signing a $m \in \{0,1\}^*$, determining $h = h(m) \in G$, selecting a random $r \in Z_P^*$ and setting $h' = r \cdot h \in G$, wherein said first data includes h' and Z_P^* is a multiplicative group.

10. **(Original)** The computer-readable medium as recited in claim 9, wherein said parameter data establishes a base group G of order p and generator g as system parameters for said signature generating logic.

11. **(Previously Amended)** The computer-readable medium as recited in claim 10, wherein determining said private key data and said public key data further includes:

picking

$$x \xleftarrow{R} Z_P^*,$$

and

computing $v \leftrightarrow g^x$, wherein said public key data includes v , said private key data includes x , and Z_P^* is a multiplicative group.

12. **(Original)** The computer-readable medium as recited in claim 11, wherein generating second data by signing said first data further includes:

signing h' by computing $\sigma' = x \cdot h' \in G$.

13. **(Original)** The computer-readable medium as recited in claim 12, having computer-implementable instructions for performing further acts comprising:

determining if said blind digital signature is valid.

14. **(Previously Amended)** The method as recited in claim 13, wherein determining if said blind digital signature is valid further includes:

obtaining a GDH signature on h by computing $\sigma = r \cdot \sigma' \in G$ where $r' = r^{-1} \pmod{p}$ and $\sigma = x \cdot h \in G$ is a valid GDH signature on m ; and

determining if (g, v, h, σ) is a valid Diffie-Hellman tuple.

15. **(Currently Amended)** An apparatus comprising:

memory configured to store first data that is to be blindly signed; and

signature generating logic operatively coupled to said memory and configured according to parameter data so as to be capable of encrypting data based on a Jacobian of at least one curve, said parameter data causing said signature generating logic to select at least one Gap Diffie-Hellman (GDH) group of elements relating to said curve, determine private key data and corresponding public key data, and generate second data by signing said first data with said private key data, said second data having a corresponding blind digital signature, said blind digital signature having a length corresponding to a single element in said Jacobian of said at least one curve.

16. **(Previously Amended)** The apparatus as recited in claim 15 wherein said first data is generated by a second logic operatively coupled to said first logic by digitally signing a message $m \in \{0,1\}^*$, determining $h = h(m) \in G$, selecting a random $r \in Z_p^*$ and setting $h' = r \cdot h \in G$, wherein said first data includes h' , and Z_p^* is a multiplicative group.

17. **(Original)** The apparatus as recited in claim 16, wherein said parameter data establishes a base group G of order p and generator g as system parameters for said signature generating logic.

18. **(Previously Amended)** The apparatus as recited in claim 17, wherein said signature generating logic is further configured to determine said private key data and said public key data by picking

$$x \xleftarrow{R} Z_p^*,$$

and computing $v \leftrightarrow g^x$, wherein said public key data includes v , said private key data includes x , and Z_p^* is a multiplicative group.

19. **(Original)** The apparatus as recited in claim 18, wherein said signature generating logic is further configured to generate said second data by signing h' and computing $\sigma' = x \cdot h' \in G$.

20. **(Original)** The apparatus as recited in claim 15, wherein said memory and said signature generating logic are provided within a computing device.